In re Application of:

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Arndt et al

Application No.: Filed: For:	09/764179 January 17, 2001 A DJE FOR A ROTARY COMPRESSION PRESS		ss
Examiner:	Emmanual S. Luk	Emmanual S. Luk	
Group Art Unit:	1722		
Box			
Assistant Commissioner for Patents		Docket No.: H01.2B-9610-US01	
Washington, D.C. 202	31		
TO: Examiner Luk			100
Re: December 23, 200			
FACSIMILE NO.: 703-872-9310		TIME: _	
TOTAL NUMBER C	PAGES (including cover letter):		

If a fee is required, Commissioner of Patents is hereby authorized to charge Deposit Account No. 22-0350 for any required fees.

Following please find a 3 pg Amendment to the non-final Office Action mailed September

Respectfully Submitted,

VIDAS, ARRETT & STEINKRAUS, P.A.

Date: December 23, 2002

Richard Arrett Reg. No. 33,153

6109 Blue Circle Drive, Suite 2000

Minnetonka, MN 55343-9185 Telephone: (952) 563-3000

Facsimile: (952) 563-3001

LRL/tas

23,2002.

Certificate of Transmission

I hereby certify that this correspondence is being facsimile transmitted to the United States Patent and Trademark Office, Fax No.703-872-9310, on December 23, 2002.

Signature

Vulie Emerson

4420

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Arndt et al

Application No.:

09/764179

Filed:

January 17, 2001

For:

A DIE FOR A ROTARY COMPRESSION PRESS

Examiner:

Emmanual S. Luk

Group Art Unit:

1722

Box

Assistant Commissioner for Patents

Washington, D.C. 20231

Docket No.: H01.2B-9610-US01

Amendment

This amendment is in response to the office action mailed September 25, 2002.

Please amend the application as follows:

In The Claims:

Please replace claim 1 with amended claim 1 as follows:

1. A die for a rotary compression press, comprising a die holder and a die insert which is seated in an end-side bore in a front-end face of the die holder, the die insert having a trunnion-shaped projection which is seated in the end-side bore and mounted via releasable fastening means, the projection being adapted to rotate in the die bore between axially spaced stops by means of a cooperation of threaded spindle and spindle nut means and to be biased by a spring towards the front-end face.

Please replace claim 2 with amended claim 2 as follows:

2. The die according to claim 1, characterized in that that a threaded spindle is connected, in a non-rotary relationship, to a free end of the projection and the bore has disposed therein, in non-rotary relationship, a spindle nut with which the threaded spindle interacts.